



*Truck Tire Operator's Manual and Limited Warranty,
Including Applicable Limited Warranty Coverage for Commercial use,
for the Michelin® Long Haul Tires with Extended Warranty, and
for Limited Warranty Coverage for Consumer use*

▶ **MICHELIN® TRUCK TIRE LIMITED WARRANTY**

ABOUT THIS WARRANTY

As the original purchaser of a Michelin® brand truck tire, you are covered by all the benefits and conditions (subject to the maintenance recommendations and safety warnings) contained in this booklet. To ensure your understanding of and compliance with the terms and conditions of this warranty, please read it carefully. It is essential that you also read and understand the safety and maintenance recommendations for your tires beginning on page 6.

WHAT IS COVERED AND FOR HOW LONG – COMMERCIAL USE

Workmanship and Materials

Except as limited below, Michelin® truck tires bearing the Michelin® name and complete serial and identification numbers, used in commercial service according to the instructions contained in this Operator's Manual, are covered by this limited warranty against defects in workmanship and materials for the life of the original tread. At that time, all warranties, express or implied, expire.

Long Haul Tires with Extended Warranty

Certain Michelin® truck tires bearing the Michelin® name and complete serial and identification numbers, used only in long-haul service according to the instructions contained in this Operator's Manual, are covered by this limited warranty against defects in workmanship and materials for 700,000 miles, and up to 3 retreads for 7 years from the date of manufacture. At that time, all warranties, express or implied, expire. (See Reference Chart for list of tires covered by this extended warranty on page 4.)

Casings covered under this Extended Warranty which become unserviceable due to a covered condition, will be replaced under Extended Warranty coverage only if:

- 1) The tires have been used in long haul highway service for the life of the casing.
- 2) The tires have been inspected and retreaded by a participating Michelin® dealer, in accordance with the retreading standards set by the American Retreader's Association, the National

▶ **MICHELIN® TRUCK TIRE LIMITED WARRANTY**

Tire Dealers/Retreader's Association, Michelin® Retread Technologies, Inc, (MRTI), Bandag or Oliver Rubber Company, and in accordance with Michelin's specifications for the particular tire treads/sizes covered. (see retread specifications listed on page 5.)

- 3) The casings have not become unserviceable due to a condition listed under "WHAT IS NOT COVERED" (see below).

WHAT IS COVERED AND FOR HOW LONG – CONSUMER USE

Michelin® truck tires bearing the Michelin® name and complete serial and identification numbers, used in consumer service, such as on a motorhome, according to the instructions contained in this Operator's Manual, are covered by this limited warranty against defects in workmanship and materials for the life of the original tread, or five years from the date of purchase, whichever occurs first. At that time, all warranties, express or implied, expire.

Definitions

The life of the original usable tread is the original tread down to the level of the treadwear indicators - 2/32nds of an inch (1.6mm) of tread remaining. Date of purchase is documented by new vehicle registration or tire sales invoice. If no proof of purchase is available, coverage will be based on the date of manufacture, as molded on the sidewall. The date of manufacture is based on the original Michelin® DOT number molded on the tire sidewall. The mileage received will be based on fleet records. Replacement will be made in accordance with the terms and conditions described under "HOW REPLACEMENT CHARGES ARE CALCULATED."

▶ MICHELIN® TRUCK TIRE LIMITED WARRANTY

WHAT IS NOT COVERED

Tires/casings which become unserviceable due to:

- Road hazard injury (e.g., a cut, snag, bruise, impact damage or puncture);
- Incorrect mounting of the tire, tire/wheel imbalance, improper retread or improper repair;
- Misapplication, improper maintenance, racing, underinflation, over-inflation or other abuse resulting in casing damage or fatigue;
- Accident, fire, chemical corrosion, contamination, tire alteration or vandalism;
- Flat spotting caused by improper storage;
- The addition of liquid, solid or gaseous materials other than air, nitrogen or carbon dioxide;
- Uses other than long haul service for any extended warranty casing claims;

- Uneven or rapid wear caused by mechanical irregularity in the vehicle such as wheel misalignment, resulting in damage to the under-tread, carcass or steel belts;
- Ozone or weather checking.

HOW REPLACEMENT CHARGES ARE CALCULATED – COMMERCIAL AND CONSUMER USE

Workmanship/Materials

A tire which becomes unserviceable due to a condition covered by this workmanship and materials limited warranty will be replaced with a comparable new Michelin® truck tire, for a *pro rata* charge. The retailer will determine the charge by multiplying the percentage of the original usable tread worn by the current selling price at the adjustment location or the price on the current Michelin® Americas Truck Tires Base Price List, whichever is lower. This list is based on a predetermined price intended to fairly represent the actual selling price of the tire.

You pay the cost of mounting, balancing, and any other service charges and applicable taxes.

▶ MICHELIN® TRUCK TIRE LIMITED WARRANTY

Long Haul Tires with Extended Warranty

The following tire sizes are covered by the 700,000 mile/7 year/3 retread warranty.

Tread Design	Size	Load Range
XZA2	11R22.5	G, H
XZA2	11R24.5	G
XZA2	275/80R22.5	G, H
XZA2	275/80R24.5	G
XZA3	11R22.5	G, H
XZA3	11R24.5	G
XZA3	275/80R22.5	G, H
XZA3	275/80R24.5	G

Tread Design	Size	Load Range
XDA2	11R22.5	G
XDA2	11R24.5	G
XDA2	275/80R22.5	G
XDA2	275/80R24.5	G
XDA3	11R22.5	G
XDA3	11R24.5	G
XDA3	275/80R22.5	G
XDA3	275/80R24.5	G
XDA Energy	275/80R22.5	G

If your Long Haul tire becomes unserviceable due a condition covered by this warranty before providing 700,000 miles and 3 retreads of service, Michelin® will provide casing credit based on the following schedule:

Life of casing up to 7 years

Original Tread

First, second or third retread

Casing Credit

\$130.00

\$100.00

WHAT YOU MUST DO WHEN MAKING A CLAIM

When making a claim under the terms of this limited warranty you must present your tire/casing to a participating Michelin® truck tire retailer. **You pay any service charges for normal vehicle and tire maintenance.**

CONDITIONS AND EXCLUSIONS

Unless this limitation is prohibited by state law, this warranty does not provide compensation for loss of time, loss of use of vehicle, inconvenience or incidental or consequential damages.

Tires/casings presented for claim remain the property of the owner/consumer and Michelin® brand accepts no responsibility for loss of, or damage to, tires/casings, which are in the custody or control of a Michelin® truck tire retailer for the purpose of inspection for warranty adjustment. Tires accepted for claim become the property of Michelin® North America, Inc. ("MNA").

▶ **MICHELIN® TRUCK TIRE LIMITED WARRANTY**

In the event of a disputed claim, the owner/consumer must make the tire available for further inspection.

No Michelin® representative, employee or retailer has the authority to make or imply any representation, promise or agreement, which in any way varies the terms of this limited warranty.

This limited warranty applies only in the United States.

CONSUMER RIGHTS

This limited warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

SAFETY MAINTENANCE INFORMATION

Read your Tire Operator's Manual, the information on the sidewall of your tires, your vehicle owner's manual and vehicle tire information placard for essential safety and maintenance information.

When service is required:

1. Contact a participating Michelin® truck tire retailer listed in your yellow pages.

2. If additional assistance is needed in locating a Michelin® truck tire retailer, please call the phone number for your area which is listed on page 14 or write Consumer Relations at the address listed on page 14.

MICHELIN® RETREAD SPECIFICATIONS FOR ALL SIZES OF EXTENDED WARRANTY TIRES*:

- Buff radius: 675 mm.
 - Buffing rim width: 9.0"
 - Buffing inflation pressure: 1.2 to 1.5 bar.

 - Minimum undertread thickness: 0.5 mm.
 - Maximum undertread thickness: 4.0 mm.

 - Minimum pre-cure cap width: 219 mm.
 - Maximum pre-cure cap width: 232 mm.
- * This is the preferred specification.



WARNING

Disregarding any of the safety precautions and instructions contained in this manual may result in tire failure or explosion causing serious personal injury or death.

▶ DRIVING ON ANY TIRE THAT DOES NOT HAVE THE CORRECT INFLATION PRESSURE IS DANGEROUS

Any underinflated tire builds up excessive heat that may result in sudden tire destruction. For replacement tires, the correct inflation pressure will be provided by your tire retailer. If not, refer to the vehicle placard.

The placard indicates the minimum inflation pressures which must be maintained. However, do not exceed the maximum inflation pressure for the tire or for the wheel on which it is mounted.

▶ CHECK THE COLD INFLATION PRESSURES IN ALL YOUR TIRES, INCLUDING THE SPARE, AT LEAST ONCE EACH WEEK

Failure to maintain correct inflation pressure may result in improper vehicle handling and may cause rapid and irregular tire wear, sudden tire destruction, loss of vehicle control and serious personal injury. Therefore, inflation pressures should be checked at least once each week and always prior to long distance trips.

Pressures should be checked when tires are cold; in other words, before they have been driven on. The ideal time to check tire pressures is early morning. Driving, even for a short distance, causes tires to heat up and air pressure to increase.

Never bleed air from hot tires. Bleeding air from hot tires could result in underinflation.

Use an accurate tire gauge to check pressures. Never allow children to inflate or deflate tires.

If your pressure check indicates that one of your tires has lost pressure of four pounds or more, look for signs of penetration, valve leakage or wheel damage that may account for the air loss.

Any tire suspected of having been run flat or run at very low air pressure (less than 80% of normal operating pressure) should not be re-inflated without careful inspection of the entire tire. Visit a Michelin® Truck Tire retailer.

▶ **INSPECT YOUR TIRES DAILY. IF YOU SEE ANY DAMAGE TO YOUR TIRES OR WHEELS, VISIT A MICHELIN® TRUCK® TIRE DEALER AT ONCE.**

Hazards

Driving over potholes, curbs, glass, metal, rocks, wood debris and the like, can damage a tire and should be safely avoided. Unavoidable contact with such hazards should prompt a thorough tire inspection.

If you see damage to your tires or wheels, replace with a spare and immediately visit any participating Michelin® Truck Tire retailer for advice.

Inspection

Always examine your tires for bulges, cracks, cuts, pene-

trations and abnormal tire wear, particularly on the edges of the tire tread, which may be caused by misalignment or underinflation. If any such damage is found, the tire must be inspected by any participating Michelin® Truck Tire retailer at once. Use of a damaged tire could result in sudden tire destruction and rapid air loss. Failure to control a vehicle when one or more tires experience a sudden air loss can lead to an accident.

All tires will wear out faster when subjected to high speeds as well as hard cornering, rapid starts, sudden stops, frequent driving on surfaces which are in poor condition, and off-road use. Surfaces with holes and rocks or other objects can damage tires and cause vehicle misalignment. When driving on such surfaces, drive carefully and slowly, and before driving again at normal or highway speeds, examine your tires for any damage, such as cuts, bulges, penetrations, unusual wear patterns, etc.

▶ **WEAR BARS**

Michelin® truck tires contain "Wear-Bars" in the grooves of the tire tread which show up when only 2/32nds of an inch (1.6mm)

of tread is remaining. At this stage, tires must be replaced. Tires worn beyond this stage are dangerous.

(Federal law requires the tires on front axles of a Bus, Truck or Truck Tractor to have at least 4/32nds of an inch of tread depth remaining.)

► **HIGH SPEED DRIVING CAN BE DANGEROUS**

Correct inflation pressure is especially important. However, at high speeds, even with the correct inflation pressure, a road hazard, for example, is more difficult to avoid and if contact is made, has a greater chance of causing tire damage than at a lower speed. Moreover, driving at high speed reduces the reaction time available to avoid accidents and bring your vehicle to a safe stop.

If you see any damage to a tire or wheel, replace it with the spare at once and visit a participating Michelin® truck tire retailer.

The maximum speed at which Michelin® truck tires can be operated is indicated in the Michelin® Commercial Light Truck and Truck Tire Data Book. This speed varies for each type of tire and depends on the type of application. Consult a Michelin® truck tire dealer for

assistance in determining the maximum speed for your application. **Exceeding this maximum speed will cause the tire to build up excessive heat, which can cause tire damage that could result in sudden air loss and rapid tire destruction. Failure to control a vehicle when one or more tires experience a sudden air loss can lead to an accident, property damage, and personal injury.**

In any case, you should not exceed reasonable speeds as indicated by the legal limits and driving conditions.

► **WHEEL ALIGNMENT, TRACKING, AND BALANCING ARE IMPORTANT FOR SAFETY AND MAXIMUM MILEAGE FROM YOUR TIRES**

CHECK HOW YOUR TIRES ARE WEARING AT LEAST ONCE EACH MONTH

If your tires are wearing unevenly, such as the inside shoulder of the tire wearing faster than the rest of the tread, your vehicle may be out of alignment. This condition not only shortens the life of your tires but also adversely affects the handling characteristics of your vehicle, which could be dangerous. If you detect

irregular wear, have the alignment of the wheels and the parallelism of the axles checked immediately. Also check to see that your tires are properly inflated. Tires which have been run underinflated will show more wear on the shoulders than in the center of the tread. Tires which have been run overinflated will show more wear in the center of the tread than on the shoulders. For optimum tire life and performance, the front end alignment on trucks equipped with Michelin® truck tires should be in accordance with the recommendations of the vehicle manufacturer. It is recommended that you have your tires and wheels dynamically balanced. Tires and wheels which are not balanced may cause steering difficulties, a bumpy ride, and irregular tire wear.

▶ **DO NOT OVERLOAD - DRIVING ON ANY OVERLOADED TIRE IS DANGEROUS**

The maximum load rating marked on the tire sidewall of any truck tire is based on a specific maximum speed of operation. Consult a Michelin® Truck Tire Data Book for complete information on allowable loads for the tires in your application. Tires which are loaded beyond their maximum allowable loads

for the particular application, will build up excessive heat that may cause sudden tire destruction, property damage, and personal injury.

Do not exceed the gross axle weight rating for any axle on your vehicle. For detailed information about weighing your Recreational Vehicle, please call the Consumer Relations telephone number listed on page 14. A free copy of the Michelin® Recreational Vehicle Tire Guide will be mailed to you.

▶ **TIRE MIXING**

FOUR WHEEL TRUCKS: For best performance it is recommended that the same size and type of tire be used on all four wheel positions. If only two Michelin® radial truck tires are mounted with two non-radial tires, the radial tires should be mounted on the rear axle.

Before mixing different types of tires in any configuration on any vehicle, be sure to check the vehicle manufacturer's owner's manual for its recommendations.

It is especially important to check the vehicle manufacturer's owner's manual when mixing, matching or replacing tires on 4-wheel drive vehicles, as this may require special precautions.

TRUCKS WITH MORE THAN FOUR WHEEL POSITIONS:

For best performance, it is strongly recommended that radial and non-radial tires not be mixed in a dual fitment.

▶ TIRE ALTERATIONS

Do not make or allow to be made any alteration to your tires. Alterations may prevent proper performance, leading to tire damage which can result in an accident. Tires which become unserviceable due to alterations such as, but not limited to, truing, whitewall inlays, addition of balancing or sealant liquids or the use of tire dressings containing petroleum distillates, are excluded from warranty coverage.

▶ IMPROPERLY RETREADED AND/OR REPAIRED TIRES ARE DANGEROUS AND CAN CAUSE TIRE DESTRUCTION, PROPERTY DAMAGE, AND PERSONAL INJURY.

Retreading and repairing of Michelin® Truck Tires should be performed only by qualified personnel with proper equipment using the procedures contained in Michelin® Retread and Repair manuals.

If any Michelin® tire sustains a puncture, have the tire demounted and thoroughly inspected by a participating Michelin® tire retailer for possible damage that may have occurred.

Plug-only repairs done on-the-wheel are considered improper and are therefore, not recommended. Such repairs are not reliable and may cause further damage to the tire and may result in tire failure.

▶ STORAGE

Tires contain waxes and emollients to protect their outer surfaces from ozone and weather checking. As the tire rolls and flexes, the waxes and emollients continually migrate to the surface, replenishing this protection throughout the normal use of the tire. Consequently, when tires sit outdoors, unused for long periods of

time (a month or more) their surfaces become dry and more susceptible to ozone and weather checking, and the casing becomes susceptible to flat spotting. Serious problems occur with tube type tires when mounted with water trapped between the tire and the tube. Due to pressurization, the liquid can pass through the inner liner and into the casing plies. **For these reasons, tires should always be stored in a cool, dry, clean indoor environment. If storage is for one month or more, eliminate the weight from the tires by raising the vehicle or by removing the tires from the vehicle. Failure to store tires in accordance with these instructions could result in premature aging of the tires and sudden tire failure.**

When tires are stored, be sure they are placed away from sources of heat and ozone, such as hot pipes and electric generators. Be sure the surfaces on which tires are stored are clean and free from grease, petroleum products or other substances which could deteriorate the rubber. **(Tires exposed to these materials during storage or driving could be subject to sudden failure.)**

▶ FOLLOW THESE MOUNTING RECOMMENDATIONS TO PREVENT TIRE DESTRUCTION, PROPERTY DAMAGE AND PERSONAL INJURY

Regulations and recommendations published by the Occupational Safety and Health Administration of the U.S. Department of Labor (OSHA) deal in detail with mounting and demounting of tires for trucks. You should ensure that you are always in compliance with these regulations and recommendations. In addition, Michelin® urges you to bear in mind the following considerations:

Tire changing can be dangerous and must be done by professionally trained persons using proper tools and procedures as specified by the Rubber Manufacturers Association (RMA).

Tires should be mounted on wheels of the correct size and type which are in good, clean condition. Bent, chipped or rusted wheels, rims or rim components may cause tire damage and can also malfunction causing an accident.

All rim components (i.e. flanges, lock rings, rim base, etc.) must

match. Be sure to check rim/wheel manufacturer's specifications.

When changing any tire, always deflate the tire before loosening any wheel or rim lugs. Always install new valve cores with new mountings.

TUBES: Always fit a new Michelin® tube of the proper size in a new mounting. A tube through normal use will experience growth; therefore, if an old tube is re-used, there is a probability of creasing it with subsequent chafing and eventual failure of the tube causing tire damage. Michelin® tubes are made of butyl rubber and marked with the trade name "AIRSTOP®". Because of the extreme flexibility of the Michelin® 'X'® tire, it is essential to use an "AIRSTOP®" tube. These tubes are made with an overlap splice which is stronger than the butt splice used in many other tubes. The use of other tubes, not designed for Michelin® 'X' radial tires, could result in tube failure causing tire damage.

FLAPS: Always install a new Michelin® Flap when you install a new tire. A flap through extended use becomes hard and brittle. After a limited time it will develop a set to match

the tire and rim in which it is fitted; therefore, it will not exactly match a new tire/rim combination.

LUBRICANT: Always use a proper lubricant when mounting tires. Use only a approved tire mounting lubricant. Never use anti-freeze, silicones or petroleum-based lubricants. Do not allow excess lubricant to run down and collect inside the tire.

SAFETY CAGE: Always use a safety cage when inflating a truck tire. Never stand over the tire or in front of the valve when inflating. Use an inline gauge and stand to the side. Before final inflation, check the assembly carefully for signs of weakness or irregularities.

VALVE CAPS: It is essential that all valves be fitted with pressure-sealing metal valve caps, which are the PRIMARY seal of the valve, to avoid leaks. After mounting, check the assemblies for leaks. When wheel assemblies are mounted on a vehicle, be sure that the valves do not touch the brake drums or any mechanical part of the vehicle.

DUAL MOUNTING: Tires mounted in duals must be matched so that the maximum difference between the diameters of the tires does not exceed 1/4 inch. Failure to properly match dual tires will result in the tire with the larger diameter carrying a disproportionate share of the load which can cause sudden tire destruction, property damage, and personal injury.

Proper dual spacing must be provided to prevent the tires from rubbing together and to allow for the flow of cooling air. Consult the Michelin® Truck Tire Data Book or visit a Michelin® Truck Tire retailer for information on the minimum dual spacing required for a particular tire/wheel fitment.

PREPARATION OF WHEELS AND RIMS

Prior to fitment, wheel assemblies should be thoroughly inspected for cracks, warpage, deformation of flanges, side rings, lock rings, etc. The condition of the stud holes on wheels should

also be checked. If any of these conditions are discovered, the rim/wheel should be discarded. All burrs, welds, hammer dents, etc., that are present on the tire side of the rim must be made smooth with a file and/or emery cloth. Remove rust with a wire brush and apply a rust inhibiting paint.

FAILURE TO OBSERVE ANY OF THE RECOMMENDED PRECAUTIONS CONTAINED IN THIS OWNER'S MANUAL CAN LEAD TO ERRATIC VEHICLE BEHAVIOR AND/OR TIRE DAMAGE POSSIBLY RESULTING IN AN ACCIDENT.

Any time you see damage to your tires or wheels, contact your local participating Michelin® truck tire retailer listed in the yellow pages at once. If further assistance is required, contact:

In the United States 1-888-622-2306

Or Write: Consumer Relations
 P.O. Box 19001
 Greenville, SC 29602-9001

INDEX

	Page
Alterations	10
High Speed Driving	8
Inflation	6-7
Mounting	11-13
Overload	9
Preparation of Wheels & Rims	13
Retreads & Repairs	10
Storage	10-11
Tire & Wheel Inspection	7
Tire Mixing	9-10
Warranty	1-5
Wear Bars	7-8
Wheel Alignment	8-9
Wheel Balance	8-9

REMEMBER . . . TO AVOID DAMAGE TO YOUR TIRES AND POSSIBLE ACCIDENT:

- CHECK TIRE PRESSURES AT LEAST ONCE EACH WEEK WHEN TIRES ARE COLD;
- DO NOT UNDERINFLATE;
- DO NOT OVERLOAD;
- DRIVE AT MODERATE SPEEDS, OBSERVE LEGAL SPEED LIMITS;
- AVOID DRIVING OVER POTHoles, OBSTACLES, CURBS OR EDGES OF PAVEMENT;
- IF YOU SEE ANY DAMAGE TO A TIRE, REPLACE WITH A SPARE AND VISIT ANY MICHELIN® TRUCK TIRE DEALER AT ONCE;
- IF YOU HAVE ANY QUESTIONS, CONTACT YOUR MICHELIN® TRUCK TIRE DEALER.

MICHELIN® NORTH AMERICA

P.O. BOX 19001, GREENVILLE, SOUTH CAROLINA 29602-9001